

THE NEW 3 IN 1 PRIMER

FOR EASY FILLING/PRIMING



THE NEW 3IN1 PRIMER SHADE

MADE FOR PROFESSIONALS'



1K 3 IN 1 PRIMER SHADE

3 in 1 Primer / Filler designed for easy and convenient priming / filling of different surfaces. It offers excellent adhesion and sanding properties as well as high filling power.

ADVANTAGES:

- Direct to metal, aluminium, steel and various plastics
- High filling power
- Fast drying
- Good stability on vertical surfaces
- Excellent sanding properties
- Can be topcoated with both solvent and waterborne basecoats as well as single stage topcoats



AVAILABLE IN 3 COLORS:



THE VARIATOR NOZZLE:

The spray direction and the spray size can be adjusted optimally to the damage area and size, simply, easily and quickly:

- Horizontal and vertical adjustable spray direction
- Stepless (from maximum to minimum) settable spray pattern size
- The size of the spray pattern can also be modified by means of the spray distance



DIRECT TO DIFFERENT SURFACES:



aluminium



plastic - no adhesion promoter required



metal

VIDEO:



before



in process



after

more information and application video



1K 3 IN 1 PRIMER SHADE

Part-No.:	Color	Filling
3680403	white	423 g /14.9 oz
3680404	gray	423 g /14.9 oz
3680405	black	423 g /14.9 oz



Description

3 in 1 Primer / Filler designed for easy and convenient priming / filling of different surfaces. It offers excellent adhesion and sanding properties as well as high filling power.

	<p>Preparation Remove any visible rust, sand substrates with P180 - P240 abrasive paper, clean and degrease</p>
	<p>Shake and spray to test Shake can thoroughly for at least 2 minutes from when the agitation balls are heard. After shaking the can, test spray and check compatibility with the surface and the colour.</p>
	<p>Spraying distance 4 - 6 inches / 10 - 15 cm</p>
	<p>Spray passes Dry film thickness 1.6 - 2.4 mil (40 - 60 µm) (approx. 2 - 3 spray coats)</p>
	<p>Drying dust dry: 7 - 8 min dry to touch: approx. 30 - 40 min Ready for sanding: approx. 50 - 60 min</p>
	<p>Continue Wet sanding or dry sanding with P 400 - P 500</p>
	<p>Shelf Life 60 months / 60° F - 77° F / 15 - 25° C</p>

Note

For professional use only. Identification, see safety data sheet.

Peter Kwasny Inc.

62-64 Enter Lane
Islandia, NY 11749

Phone: +1 844-426-6330

Fax: +1 866-226-6434
service@kwasny.us

www.spraymax.com

For orders: Toll free North America 1-844-426-6330 / order@kwasny.us



Peter Kwasny Spraypaint Canada Inc.

40 University Avenue,
Suite 904
Toronto ON M5J 1T1

Phone: +1 844-426-6330

Fax: +1 866-226-6434
service@kwasny.us

www.spraymax.com

Téléphonez gratuitement en Amérique du Nord: 1-844-426-6330 / order@kwasny.us